The School District of Palm Beach County Project Name: SDPBC Project No.:

SECTION 26 41 00 LIGHTNING PROTECTION for STRUCTURES

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Grounding and bonding for lightning protection
- B. Air terminals and interconnecting conductors
- 1.2 RELATED SECTIONS
 - A. Section 07 52 00 Roofing systems
- 1.3 REFERENCES
 - A. LPI-175 Lightning Protection Installation Standard
 - B. LPI-177 Inspection Guide for LPI Certified Systems
 - C. NFPA 780 Lightning Protection Code
 - D. UL 96 Standard for Lightning Protection Components
 - E. UL 96A Standard for Installation Requirements for Lightning Protection Systems
- 1.4 SYSTEM DESCRIPTION
 - A. Lightning Protection systems: Provide conductor system protecting roofs consisting of air terminals on roofs, roof-mounted mechanical equipment, chimneys, stacks, steeple, parapets, and penthouse roofs; bonding of structure and other metal objects; grounding electrodes; interconnecting conductors, and irrigation pumps and structure.

1.5 SUBMITTALS

- A. Section 01 33 00 Submittals Procedures for submittals.
- B. Shop Drawings:
 - 1. Indicate layout of air terminals, grounding electrodes, and bonding connections to structure and other metal objects.
 - 2. Include terminal, electrode, and conductor sizes and connection and termination details.
- C. Product Data: Provide dimensions and materials of each component, and include indication of listing in accordance with UL 96.
- 1.6 PROJECT RECORD DOCUMENTS
 - A. Submit under Provisions of Section 01 33 00.
 - B. Record the actual locations of air terminals, grounding electrodes, bonding connections, and routing of system conductors in project record documents.
- 1.7 QUALITY ASSURANCE
 - A. Perform work in accordance with NFPA 780.
 - B. Perform work in accordance with UL 96A and provide master label.
 - C. Perform work in accordance with LPI-175 and provide LPI certification.
 - D. Maintain one copy of each document on site.
- 1.8 QUALIFICATIONS
 - A. Manufacturer: Company specializing in lightning protection equipment with minimum three years documented experience and member of the Lightning Protection Institute.
 - B. Installer: Authorized installer of manufacturer with minimum three years documented experience and certified by the Lightning Protection Institute.
- 1.9 FIELD MEASUREMENTS
 - A. Verify that field measurements are as indicated on shop drawings.
- 1.10 COORDINATION
 - A. Coordinate work with roofing, exterior, and interior finish installations.

The School District of Palm Beach County Project Name: SDPBC Project No.:

PART 2 PRODUCTS

2.1 COMPONENTS

- A. Air Terminals: Provide either solid copper or aluminum with adhesive bases for single-ply roof installations.
- B. Air Terminal for Chimney: Lead-coated copper
- C. Decorations: Ball
- D. Grounding Rods: Solid copper
- E. Ground Plate: Copper
- F. Grounding down conductors and grounding ring electrodes: Copper.
- G. Conductors except those noted above copper or aluminum.
- H. Connectors and Splicers: Bronze

PART 3 EXECUTION

3.1 INSTALLATION

- A. Install in accordance with NFPA 780, UL 96A, and LPI-175.
- B. Connect conductors using exothermic welding process.
 - 1. Protect adjacent construction elements and finishes from damage.
- C. Bond exterior metal bodies on building to the lightning protection system, and provide intermediate level interconnecting loops 60' (18 m) on center.
- D. Do not install copper lightning protection materials on aluminum roofing, siding, or other aluminum surfaces.
- E. Do not install aluminum lightning protection materials on copper surfaces.
- F. Protect copper components installed within 24" of the top of a chimney or vent emitting corrosive gases by a hot-dipped lead coating or equivalent.
- G. Down conductors shall be routed concealed in PVC sleeves installed in the structure.
- H. Connect conductor to metal bodies of conductance located within 6' by secondary conductor.
- I. Provide lightning protection for buildings, covered walkways, press boxes, scoreboards, and all other structures required by NFPA 780.
- 3.2 FIELD QUALITY CONTROL
 - A. Obtain the services of Underwriters Laboratories, Inc. to provide inspection and labeling of the lightning protection system in accordance with UL 96A.
 - B. Perform inspection and testing in accordance with NFPA 780.
 - C. Provide owner with an Underwriters Laboratories final certification of the lightning protection system.
 - D. Contractors' tests shall be scheduled and documented in accordance with the commissioning requirements.
 - 1. Refer to Section 01 91 00 Commissioning, for further details.

3.3 DEMONSTRATION AND TRAINING

- A. Training of the Owner's operation and maintenance personnel is required in cooperation with the Owner's Representative.
 - 1. Provide competent, factory authorized personnel to provide instruction to operation and maintenance personnel concerning the location, operation, and troubleshooting of the installed systems.
 - 2. Schedule the instruction in coordination with the Owner's Representative after submission and approval of formal training plans.

The School District of Palm Beach County Project Name: SDPBC Project No.:

- 3. Refer to Section 01 91 00, Commissioning, for further contractor training requirements.
- B. Provide demonstration and training for all types of lightning protection systems installed in this project.

END OF SECTION