The School District of Palm Beach County Project Name: SDPBC Project No.:

SECTION 26 05 19 EQUIPMENT WIRING SYSTEMS

PART 1 GENERAL

1.1 WORK INCLUDED

- A. Electrical connections to equipment specified under other Sections or furnished by Owner.
- 1.2 REFERENCES
 - A. FS W C-596 Electrical Power Connector, Plug, Receptacle, and Cable Outlet
 - B. NEMA WD 1 General Requirements for Wiring Devices
 - C. NEMA WD 5 Specific Purpose Wiring Devices

PART 2 PRODUCTS

2.1 CORDS AND CAPS

- A. Straight-blade Attachment Plug: NEMA WD 1
- B. Locking-blade Attachment Plug: NEMA WD 5
- C. Attachment Plug Configuration: Match receptacle configuration at outlet provided for equipment.
- D. Cord Construction: Oil-resistant thermoset insulated Type SO multi-conductor flexible cord with identified equipment grounding conductor, suitable for extra hard usage in damp locations.
- E. Cord Size: Suitable for connected load of equipment and rating of branch circuit over current protection.

PART 3 EXECUTION

- 3.1 INSPECTION
 - A. Verify that equipment is ready for electrical connection, wiring, and energization.
- 3.2 PREPARATION
 - A. Review equipment submittals prior to installation and electrical rough in.
 - B. Verify location, size, and type of connections.
 - C. Coordinate details of equipment connections with supplier and installer.
- 3.3 INSTALLATION
 - A. Use wire and cable with insulation listed by a nationally recognized testing lab for the installations environmental conditions.
 - B. Install pre-finished cord set where connection with attachment plug is indicated or specified, or use attachment plug with suitable strain-relief clamps.
 - C. Provide suitable strain-relief clamps for cord connections to outlet boxes and equipment connection boxes.
 - D. Make wiring connections in control panel or in wiring compartment of prewired equipment in accordance with manufacturer's instructions.
 - 1. Provide interconnecting wiring where indicated.
 - E. Install disconnect switches, controllers, control stations, and control devices such as limit switches and temperature switches as indicated.
 - 1. Connect with conduit and wiring as indicated.

END OF SECTION