## SECTION 26 05 29 HANGERS and SUPPORTS for ELECTRICAL SYSTEMS

## PART 1 GENERAL

- 1.1 WORK INCLUDED
  - A. Conduit and equipment supports
  - B. Fastening hardware
- 1.2 COORDINATION
  - A. Coordinate size, shape, and location of concrete pads with Section 03 30 00.
- 1.3 QUALITY ASSURANCE
  - A. The support systems shall be adequate for weight of equipment and conduit including any wiring they carry.

## PART 2 PRODUCTS

- 2.1 MATERIAL
  - A. Support Channel: Galvanized steel
  - B. Hardware: Corrosion resistant

## PART 3 EXECUTION

- 3.1 INSTALLATION
  - A. Fasten hanger rods, conduit clamps, and outlet and junction boxes to building structure using expansion anchors, beam clamps, spring steel clips.
  - B. Use toggle bolts or hollow wall fasteners in hollow masonry, plaster, or gypsum board partitions and walls; expansion anchors or preset inserts in solid masonry walls; self-drilling anchors or expansion anchor on concrete surfaces; sheet metal screws in metal studs; and wood screws in wood construction.
  - C. Do not fasten supports to piping, ductwork, mechanical equipment, or conduit.
  - D. Do not use powder-actuated anchors.
  - Do not drill structural steel members.
  - F. Fabricate supports from structural steel or steel channel, rigidly welded or bolted to present a neat appearance.
    - 1. Use hexagon head bolts with spring lock washers under all nuts.
  - G. Install freestanding electrical equipment on a housekeeping pad, minimum 4" thick, and 4" overhang.
  - H. Install surface mounted cabinets and panel boards with minimum of four anchors.
    - 1. Provide steel channel supports to stand cabinet ¾" off wall.
  - I. Bridge studs top and bottom with channels to support flush-mounted cabinets and panel boards in stud walls.

**END OF SECTION**